## BUYING GUIDE CHOOSE THE RIGHT ULTRADUTY™ GHS CHEMICAL LABEL

					BXEE						
	Chemical Resistant: i.e. Heptane, HCL 37%, pH3 buffer WV Resistant: 2+ years outdoor UV life										
KEY FEATURES		<b>※</b> Abrasion Re	esistant: Dry-rub a	brasion test a	nd BS5609 Sec. 3	Tear Resistant: Durable synthetic label material resists tearing					
	Waterproof: Passed BS5609 Section 2, 90-day sea water submersion adhesion test					Temperature Resistant: Apply as low as 10°F					
SURFACES	Labels adhere to metal, plastic, painted surfaces, glass, ceramic, polycarbonate and more										
SKU# (Laser) (Inkjet)	60501 60521	60502 60522	60503 60523	60504 60524	60505 60525	60506 60526	60507 60521	60508 60512	60517 60527	60518 N/A	
LAYOUT		de en Abraha en	90 - 70 ( 90 - 70)	ge en biggi Marin saga	80 C NO NO 100	(a) (b) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c					
LABEL SIZE	8-1/2" x 11"	4-3/4" x 7-3/4"	3-1/2" x 5"	4" x 4"	2" x 4"	2" x 2"	8-1/2" x 11"	8-1/2" x 14"	1" x 2-1/2"	1/2" x 1-3/4"	
LABELS/BOX	50	100	200	200	500	600	500	500	600	1500	
SHEET SIZE	8-1/2" x 11"	8-1/2" x 11"	8-1/2" x 11"	8-1/2" x 11"	8-1/2" x 11"	8-1/2" x 11"	8-1/2" x 11"	8-1/2" x 14"	8-1/2" x 11"	8-1/2" x 11"	
BS5609 SEC. 2 90-DAY SEA WATER SUBMERSION	<b>~</b>	<b>~</b>	<b>✓</b>	<b>~</b>	<b>~</b>	<b>~</b>	<b>~</b>	<b>~</b>	<b>~</b>	<b>~</b>	
BS5609 SEC. 3 CERTIFIED PRINTERS OCEAN FREIGHT	Visit avery.com/GHS for list										
TEMPERATURE	-20°F to 220°F (Laser); -40°F to 300°F (Inkjet) Please Test For Your Application										
EASY PEEL®	Back Split Liner	<b>~</b>	<b>~</b>	<b>~</b>	<b>~</b>	<b>~</b>	Back Split Liner	Back Split Liner	<b>~</b>	<b>✓</b>	
PRINT-TO-THE-EDGE		<b>~</b>		<b>~</b>		<b>~</b>			<b>✓</b>	<b>~</b>	
AVERY® GHS WIZARD SOFTWARE	FREE at www.avery.com/GHS										
SKU NUMBER	60511 60512 60513										
LAYOUT											
LABEL SIZE	8-1/2" x 11"				8-1/2" x 14"			5-1/2" x 8-1/2"			
LABELS/BOX	500				500			1000			
SHEET SIZE	8-1/2" x 11"				8-1/2" x 14"			8-1/2" x 11"			
BS5609 SEC. 2 90-DAY SEA WATER SUBMERSION	✓				✓			✓			
BS5609 SEC. 3 CERTIFIED OCEAN FREIGHT	✓				✓			✓			
TEMPERATURE	-40°F to 300°F										
AVERY® GHS WIZARD SOFTWARE	FREE at www.avery.com/GHS										

©2017 Avery Products Corporation. All rights reserved. Avery, UltraDuty and all other Avery brands, product names and codes are trademarks of CCL Label, Inc. All other brands and product names are trademarks or registered trademarks of their respective companies. Personal and company names and other information depicted on samples are fictitious. Any resemblance to actual names and addresses is purely coincidental.



